

**PRODUCT**

---

**1.8 mil General Carton Sealing Tape****DESCRIPTION**

---

Film:	1.0 mil, BOPP
Total Thickness:	1.8 mil
Adhesive:	Emulsion Acrylic
Color:	Clear, Tan

**PHYSICAL PROPERTIES**

---

Tensile Strength (lbs/in)	20 minimum	* PSTC-31
Elongation (% at break)	160 maximum	PSTC-31
180° Peel Adhesion (oz/in)	20	PSTC-1
Resistance to UV light	Excellent	

**APPLICATION TEMPERATURE \*\***

---

32° F to 140° F

**OPERATING TEMPERATURE \*\*\***

---

-10° F to 200° F

**TYPICAL APPLICATIONS**

---

For sealing boxes and other packaging applications subjected to normal shipping hazards.

**NOTES:**

The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine their suitability before adapting them on a commercial scale.

**\*PSTC: Pressure Sensitive Tape Council**

**\*\* Application Conditions:** The conditions at which the tape is being unwound and applied to the substrate. Under the specified application conditions, the tape should unwind to the substrate properly and perform as normally expected.

**\*\*\*** The tape is exposed to the operating conditions for 1 year. Under the specified operating conditions, the tape should adhere to the substrate properly and perform as normally expected.

SUP053

