

PRODUCT FACT SHEET**Provident Grade Reinforced
Water Activated (Gummed) Sealing Tape****PRODUCT****Provident Grade Reinforced Water Activated (Gummed) Tape****DESCRIPTION**

Backing: 3 way reinforcing yarns laminated between 2 sheets of 20# and 24# kraft paper with a non-asphaltic, water-resistant, flexible, and non-staining amorphous polypropylene. Yarns in the machine direction average no more than 5/8" apart. Yarns in the cross machine direction are arranged in a diamond pattern with the spacing between the parallel sides of the diamond averaging not more than 1-1/4".

Adhesive: Synthetic starch-fortified, non-toxic, and odorless

Color: Kraft - Printable

PHYSICAL PROPERTIES

| | |
|---|----|
| Tensile Strength (lbs/in) Machine Direction | 47 |
| Tensile Strength (lbs/in) Cross Machine Direction | 30 |
| Elongation (% at break) | 0 |

TYPICAL APPLICATIONS

For sealing lightweight boxes subjected to minimal shipping hazards, using a single strip, top and bottom. For sealing boxes subjected to normal shipping hazards, using three strips, top and bottom.

| Roll Lengths | Case Weights | Case Pack | Palletizing |
|----------------------------|---------------------|------------------|--------------------|
| 70mm x 137M (2.75" x 450') | 26 lbs. | 10 rolls/case | 60 cases/pallet |
| 70mm x 114M (2.75" x 375') | 17.5 lbs. | 8 rolls/case | 60 cases/pallet |
| 76mm x 137M (3" x 450') | 28 lbs. | 10 rolls/case | 60 cases/pallet |

NOTES:

The information listed above has been obtained from controlled laboratory tests and is reliable, but should not be used for the purpose of writing specifications. It is offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. It is recommended that the prospective user determine their suitability before adapting them on a commercial scale.

WAT040



SEKISUI TA INDUSTRIES, INC.
100 SOUTH PUENTE STREET • BREA, CA 92821
(800) 258-8273 / (714) 255-7888 PHONE • (800) 235-8273 FAX